Author Index

Addison, P. S.	Wavelet analysis of the breakdown of a pulsed vortex flow	217–229
Ahmad-Shariff, A.	Comparison of experimental assessment methods to estimate the strength of gear teeth	291–301
Akiyama, M.	Investigation and improvement of the resistance against crack propagation for a hot steel rolling tool material	629–637
Ali, A. R. M.	Theoretical and experimental results of the elastic–plastic response of a circular rod subjected to non-proportional combined torque and tension loadings	251–261
Al-Shukri, S. M.	Effects of sandpaper roughness and stream turbulence on the turbulent boundary layer	507–515
Arafa, M. H.	Evaluation of spur gear mesh compliance using the finite element method	569–579
Ashby, R.	Comparison of experimental assessment methods to estimate the strength of gear teeth	291–301
Bakhtar, F.	On the performance of a cascade of turbine rotor tip section blading in wet steam. Part 4: droplet measurements	343–353
Balkwill, J. D. G.	Dynamic analysis of rotationally flexible cam mechanisms	537–550
Bayley, F. J.	Flows and temperatures in compressor and turbine wheelspaces	451–460
Benhamza, M. E. H.	Flow characteristics inside a diffuser of complex shape	277–289
Bernhardt, G.	A theoretical formula for calculating damping in the impact of two bodies in a multibody system	211–216
Brandon, J. A.	Spectral indicators in structural damage identification: a case study	411–415
Burrows, C. R.	Dynamic modelling of flexible structures using a local frame formulation	645–654
Calvert, W. J.	Transonic fan and compressor design	419–436
Came, P. M.	Centrifugal compressor design	139–155
Casey, M. V.	Radial compressor design for industrial compressors	71–83
Chakraverty, S.	Vibration of non-homogeneous plates using two-dimensional orthogonal polynomials as shape functions in the Rayleigh–Ritz method	707–714
Chawdhry, P. K.	Dynamic modelling of flexible structures using a local frame formulation	645–654
Chen, C.-S.	Regular and chaotic dynamics of a simplified fly-ball governor	461–475
Chen, H.-H.	Regular and chaotic dynamics of a simplified fly-ball governor	461–475
Chen, J. Q.	Walking machine leg design: the effect of leg geometry on knee torque	581–590
Chen, W. L.	On the tuning pipe of a two-stroke engine for scooter-type motorcycles	861–866
Childs, P. R. N.	Heat flux measurement techniques	655–677
Chochia, G. A.	Dynamic modelling of flexible structures using a local frame formulation	645–654
Dalbert, P.	Radial compressor design for industrial compressors	71–83
Dalgarno, K. W.	Tangential slip noise of V-ribbed belts	741–749
Dawes, W. N.	Computational fluid dynamics for turbomachinery design	107–124
Day, A. J.	Tangential slip noise of V-ribbed belts	741–749
Denton, J. D.	Computational fluid dynamics for turbomachinery design	107–124
Denton, J. D.	The exploitation of three-dimensional flow in turbomachinery design	125–137
Dowson, D.	A loose-ring lubricator model	199–209
Dowson, D.	A full numerical analysis of hydrodynamic lubrication in artificial hip joint replacements constructed from hard materials	355–370
Drtina, P.	Hydraulic turbines—basic principles and state-of-the-art computational fluid dynamics applications	85–102
Dumoulin, S.	Bidimensional strain measurement using digital images	811–817
Ebrahimi, M.	Computation of the series impedance matrix	795–809
Flaxington, D.	Turbocharger aerodynamic design	43–57
French, M.	A measure of utility of parts of plane frames	623–628
Gallimore, S. J.	Axial flow compressor design	437–449
Gaskell, P. H.	A fine element analysis of steady viscous flow in triangular cavities	263–276
Gaskell, P. H.	Numerical predictions of a turbulent diffusion flame in a cylindrical combuster using eddy dissipation and flamelet combustion models	697–705
Ge, Z.-M.	Regular and chaotic dynamics of a simplified fly-ball governor	461–475
Gibbings, J. C.	Effects of sandpaper roughness and stream turbulence on the turbulent boundary layer	507–515
Ginder, R. B.	Transonic fan and compressor design	419–436
Gorman, D. G.	Analysis of the vibration of pipes conveying fluid	849–860

© IMechE 1999

Goto, A.	On the role of three-dimensional inverse design methods in turbomachinery shape optimization	27–42
Greenwood, J. R.	Heat flux measurement techniques	655–677
Greim, R.	Aerodynamic design of 50 per cent reaction steam turbines	1–25
Gülich, J. F.	Impact of three-dimensional phenomena on the design of rotodynamic pumps	59–70
Hale, J. M.	A novel thick-film strain transducer using piezoelectric paint	613–622
Hampartsoumian, E.	Numerical predictions of a turbulent diffusion flame in a cylindrical combustor using eddy dissipation and flamelet combustion models	697–705
Harada, H.	On the role of three-dimensional inverse design methods in turbomachinery shape optimization	27–42
Hashmi, M. S. J.	Theoretical and experimental results of the elastic–plastic response of a circular rod subjected to non-proportional combined torque and tension loadings	251–261
Havakechian, S.	Aerodynamic design of 50 per cent reaction steam turbines	1–25
Hesketh, J. A.	Design of low-reaction steam turbine blades	157–174
Hills, D. A.	Elastic contact on a double-layered substrate	331–342
Hooke, C. J.	The behaviour of heavily loaded line contacts with transverse roughness	309–320
Howard, D.	Walking machine leg design: the effect of leg geometry on knee torque	581–590
Howson, W. P.	Exact dynamic stiffness method for planar natural frequencies of curved Timoshenko beams	687–696
Hsu, M.-P.	On the tuning pipe of a two-stroke engine for scooter-type motorcycles	861–866
Huang, R. F.	On the tuning pipe of a two-stroke engine for scooter-type motorcycles	861–866
Hui, H.	Changes to the vortical and turbulent structure of jet flows due to mechanical tabs	321–329
Innes, G. E.	A loose-ring lubricator model	199–209
Jemah, A. K.	Exact dynamic stiffness method for planar natural frequencies of curved Timoshenko beams	687–696
Jiang, K.	A parallel parking system for a car-like robot with sensor guidance	591–600
Jin, Z. M.	A full numerical analysis of hydrodynamic lubrication in artificial hip joint replacements constructed from hard materials	355–370
Kelly, P. A.	Elastic contact on a double-layered substrate	331–342
Khezzar, L.	Flow characteristics inside a diffuser of complex shape	277–289
Kmeci, T.	Radial compressor design for industrial compressors	71–83
Kobayashi, T.	Changes to the vortical and turbulent structure of jet flows due to mechanical tabs	321–329
Kubie, J.	A model of liquid outflow from single-outlet vessels	833–847
Kwan, A. S. K.	Spectral indicators in structural damage identification: a case study	411–415
Lee, K.	On the tuning pipe of a two-stroke engine for scooter-type motorcycles	861–866
Lee, S.-C.	Regular and chaotic dynamics of a simplified fly-ball governor	461–475
Lee, S. W.	New error correction algorithms minimizing residual positional error for a computer integrated error calibration/correction system in computer numerically controlled machine tools	679–686
Le-Ngoc, L.	Self-induced vibration of bandsaw blades during cutting	371–380
Liang, Q. Q.	Optimal selection of topologies for the minimum-weight design of continuum structures with stress constraints	755–762
Liew, Z. F. K.	Non-reversible dry friction oscillator: design and measurements	527–534
Lin, X. B.	Direct simulation of fatigue crack growth for arbitrary-shaped defects in pressure vessels	175–189
Long, C. A.	Heat flux measurement techniques	655–677
Lopes, E. M. O.	Spectral indicators in structural damage identification: a case study	411–415
Ma, C. Y.	Numerical predictions of a turbulent diffusion flame in a cylindrical combustor using eddy dissipation and flamelet combustion models	697–705
McCallion, H.	Self-induced vibration of bandsaw blades during cutting	371–380
McNeil, D. A.	A slip with entrained liquid fraction approach to compressible two-phase flow in nozzles	729–740
Mahmud, T.	Numerical predictions of a turbulent diffusion flame in a cylindrical combustor using eddy dissipation and flamelet combustion models	697–705
Marquis, A. J.	Flow characteristics inside a diffuser of complex shape	277–289
Mase, T.	Investigation and improvement of the resistance against crack propagation for a hot steel rolling tool material	629–637
Megahed, M. M.	Evaluation of spur gear mesh compliance using the finite element method	569–579
Metcalfe, A. V.	Comparison of experimental assessment methods to estimate the strength of gear teeth	291–301
Meunier, M.	Free vibration analysis of composite sandwich plates	715–727
Mguil-Touchal, S.	Bidimensional strain measurement using digital images	811–817
Mimmi, G.	Analytical model of a particular type of positive displacement blower	517–526
Mitchell, D.	Computation of the series impedance matrix	795–809
Moore, R. B.	Tangential slip noise of V-ribbed belts	741–749
Morestin, F.	Bidimensional strain measurement using digital images	811–817
Morrey, D.	Dynamic analysis of rotationally flexible cam mechanisms	537–550

© IMechE 1999

Morrish, L.	Gear transmission error outside the normal path of contact due to corner and top contact	389–400
Munro, R. G.	Measuring the kinematic accuracy of worm gears	381–388
Munro, R. G.	Gear transmission error outside the normal path of contact due to corner and top contact	389–400
Munro, R. G.	A systematic approach to profile relief design of low and high contact ratio spur gears	551–562
Munro, R. G.	A new type of profile relief for high contact ratio spur gears	563–568
Na, S.-J.	A study on the numerical analysis of thermomechanical behaviour in a stud-to-plate laser braze joint	763–774
Nakamura, Y.	Static characteristics of a piston-type pilot relief valve	231–239
Nevalainen, P.	Variable step Rosenbrock algorithm for transient response of damped structures	191–198
O'Connor, J. J.	Elastic contact on a double-layered substrate	331–342
Oldroyd, A.	A numerical analysis of vortex shedding within a confined channel flow	477–490
Pahk, H. J.	New error correction algorithms minimizing residual positional error for a computer integrated error calibration/correction system in computer numerically controlled machine tools	679–686
Palmer, D.	Gear transmission error outside the normal path of contact due to corner and top contact	389–400
Pan, D.	Design considerations for the volutes of centrifugal fans and compressors	401–410
Park, J. S.	A study on the numerical analysis of thermomechanical behaviour in a stud-to-plate laser braze joint	763–774
Parker, K.	The effect of longitudinal microstriations and their profiles on the drag of flat plates	775–785
Pennacchi, P.	Analytical model of a particular type of positive displacement blower	517–526
Petrucci, G.	On the estimation of the fatigue cycle distribution from spectral density data	819–831
Petyt, M.	Vibration of non-homogeneous plates using two-dimensional orthogonal polynomials as shape functions in the Rayleigh–Ritz method	707–714
Piché, R.	Variable step Rosenbrock algorithm for transient response of damped structures	191–198
Rassam, S. Y.	On the performance of a cascade of turbine rotor tip section blading in wet steam. Part 4: droplet measurements	343–353
Reese, J. M.	Analysis of the virbation of pipes conveying fluid	849–860
Ribi, B.	Radial compressor design for industrial compressors	71–83
Robinson, C. J.	Centrifugal compressor design	139–155
Sallaberger, M.	Hydraulic turbines—basic principles and state-of-the-art computational fluid dynamics applications	85–102
Sami, M.	Three-dimensional kinetic theory approach for laser pulse heating	491–506
Sanger, D. J.	Walking machine leg design: the effect of leg geometry on knee torque	581–590
Savage, M. D.	A finite element analysis of steady viscous flow in triangular cavities	263–276
Sayers, A. T.	The effect of longitudinal microstriations and their profiles on the drag of flat plates	775–785
Scanlon, T. J.	A numerical analysis of vortex shedding within a confined channel flow	477–490
Seneviratne, L. D.	A parallel parking sysem for a car-like robot with sensor guidance	591–600
Shen, G.	Changes to the vortical and turbulent structure of jet flows due to mechanical tabs	321–329
Shenoi, R. A.	Free vibration analysis of composite sandwich plates	715–727
Sin, V. W. T.	A symmetrically piecewise linear oscillator: design and measurement	241–249
Sin, V. W. T.	Non-reversible dry friction oscillator: design and measurements	527–534
Smith, R. A.	Direct simulation of fatigue crack growth for arbitrary-shaped defects in pressure vessels	175–189
Stephens, A. E.	Spectral indicators in structural damage identification: a case study	411–415
Steven, G. P.	Optimal selection of topologies for the minimum-weight design of continuum structures with stress constraints	755–762
Stickland, M. T.	A numerical analysis of vortex shedding within a confined channel flow	477–490
Swailes, D. C.	Comparison of experimental assessment methods to estimate the strength of gear teeth	291–301
Swain, E.	Turbocharger aerodynamic design	43–57
Taylor, C. M.	A loose-ring lubricator model	199–209
Thompson, H. M.	A finite element analysis of steady viscous flow in triangular cavities	263–276
Torrance, A. A.	Influence of form on surface temperatures in form grinding	601–611
Tsubouchi, K.	Investigation and improvement of the resistance against crack propagation for a hot steel rolling tool material	629–637
Tuck, J.	A novel thick-film strain transducer using piezoelectric paint	613–622
Vacher, P.	Bidimensional strain measurement using digital images	811–817
Walker, P. J.	Design of low-reaction steam turbine blades	157–174
Walsh, D.	Influence of form on surface temperatures in form grinding	601–611
Wang, L. Q.	A more accurate method for predicting the stresses in a flat steel ribbon wound pressure vessel	787–793
Washio, S.	Static characteristics of a piston-type pilot relief valve	231–239
Whalley, R.	Computation of the series impedance matrix	795–809
Whitehouse, D. J.	Identification of two functionally different classes of maxima in random surface waveforms	303–306
Whitfield, A.	Design considerations for the volutes of centrifugal fans and compressors	401–410

© IMechE 1999

Wiercigroch, M.	A symmetrically piecewise linear oscillator: design and measurement	241–249
Wiercigroch, M.	Non-reversible dry friction oscillator: design and measurements	527–534
Wilson, M.	Design considerations for the volutes of centrifugal fans and compressors	401–410
Wu, S.	Changes to the vortical and turbulent structure of jet flows due to mechanical tabs	321–329
Xie, Y. M.	Optimal selection of topologies for the minimum-weight design of continuum structures with stress constraints	755–762
Xu, L.	The exploitation of three-dimensional flow in turbomachinery design	125–137
Xu, P.	A more accurate method for predicting the stresses in a flat steel ribbon wound pressure vessel	787–793
Yamamoto, E.	Investigation and improvement of the resistance against crack propagation for a hot steel rolling tool material	629–637
Yilbas, B. S.	Three-dimensional kinetic theory approach for laser pulse heating	491–506
Yildirim, N.	A systematic approach to profile relief design of low and high contact ratio spur gears	551–562
Yildirim, N.	A new type of profile relief for high contact ratio spur gears	563–568
Yu, Y.	Static characteristics of a piston-type pilot relief valve	231–239
Zangeneh, M.	On the role of three-dimensional inverse design methods in turbomachinery shape optimization	27–42
Zhang, D. Z.	A parallel parking system for a car-like robot with sensor guidance	591–600
Zhang, G.	On the performance of a cascade of turbine rotor tip section blading in wet steam. Part 4: droplet measurements	343–353
Zhang, S. J.	Walking machine leg design: the effect of leg geometry on knee torque	581–590
Zhang, Y. L.	Analysis of the vibration of pipes conveying fluid	849–860
Zheng, J. Y.	A more accurate method for predicting the stresses in a flat steel ribbon wound pressure vessel	787–793
Zhu, G. H.	A more accurate method for predicting the stresses in a flat steel ribbon wound pressure vessel	787–793
Zhu, S. H.	A theoretical formula for calculating damping in the impact of two bodies in a multibody system	211–216
Zuccarello, B.	On the estimation of the fatigue cycle distribution from spectral density data	819–831
Zwiebel, S.	A theoretical formula for calculating damping in the impact of two bodies in a multibody system	211–216

© IMechE 1999